



# Foshan Shunde Green Motor Technology Co., Ltd.

Fl.4, Blck. 20, Huazhi Science & Innovation Center, No. 28, Sanle Rd. East, Beijiao 528311, Shunde Foshan, China  
 http://www.greenmotortech.com Email: michelle@greenmotortech.com Tel:+86-13825520102

## GREEN MOTOR TECH - VAN



### Unit Price, EXW term for Sample

Main technical parameters		Basic configuration table of the entire vehicle		
Seating capacity (including driver)	2	1. Body: PP, PC, ABS injection molded parts cover. 2. Vehicle structure: load-bearing frame structure 3. Paint: electrophoretic framework, body baking paint 4. Glass: Front laminated glass, roof, and rear tempered glass. 5. Headlights: Combined LED headlights (steering, position, braking, lighting) 6. Front suspension: MacPherson independent suspension 7. Rear suspension: integrated shock absorption damping suspension 8. Braking: Four wheel disc brake disc hydraulic braking 9. Wheel hub: Wanyang aluminum alloy wheel hub 10. Tire: 145/70R12, radial steel wire new tire 11. Drive mode: rear axle drive 12. Radio (compatible with USB flash drive/SD card/clock) III and 203 13. Stereo sound system 14. Warm wind, natural wind. 15. Driver/passenger seat belt 16. High elasticity imitation leather car seats 17. Rear storage box, storage box under both side doors 18. Charger: Car mounted sealed 60v18A 19. Air conditioning 60V 1000W is optional. 20. Can do optional golf bag holder too.		
Overall size (L/W/H) (mm)	2700×1380×1780			
Cargo box size (mm)	1000×1200×1050			
Wheelbase (mm)	2050			
Min Ground clearance (mm)	180			
Max Speed (km/h)	40			
Min Turning radius (m)	6			
Braking distance (m)	4			
Max Climbing (%)	25			
Range (km)	120			
MOTOR	Rated power (KW)			3.0
	Rated voltage (V)			60
Battery (AH)	Maintenance free Gel Battery 60V 120AH			
Charging time	6~8 hours			
Charger (A)	60V / 18A			
Curb weight (KG)	800			
Loading weight (KG)	600			