

Performance	
Passenger capacity	23 seats (driver included)
Max.Speed	20km/h
Battery spec	(6V 220AH*16PCS), price is without battery
Climbing Ability(loaded)	20%
Braking Distance	6m
Min.Turning Radius	≤8 m
Min.Clearance	150mm
Charging time	8~10h
L×W×H	6020×1760×2250mm
F/R Tread	1490/1470mm
Axle Distance	3400 mm
Curb Weight	1975kg
Max. loading	1955kg
Standard Configurations	
Motor	96V/15KW motor
Controller	96V controller 450A
Body & Roof	High impact fiber glass
Windshield	See-through Laminated glass
Floor	High strength fiberglass plate
Seats	Sponge + artificial leather
Rear view mirror	2pcs and 1 Inner mirror
Tire	Radial tire (Auto tire), front is 185 R14LT and rear is 195R14LT.
Chassis	Welded tubular steel with rust-proof powder coated paint
Steering	Circulating ball steering gear+Power-Assisted Steering
Front Suspension	Integral front axle, coil spring+shock absorber
Rear suspension	Straight high deceleration ratio integral rear axle, steel spring cylinder type hydraulic shock absorber suspension.
Lighting system	2 headlights(big), 2 headlights(small), 2 front turn signals, 2 rear turn signals and 2 rear brake lights,2 Reversing light.
Sound system	Radio and MP3 player; Speaker
Brake system	Hydraulic double-loop four-wheel brake (with hydraulic brake power) and mechanical parking (hand brake).
Dashboard	Digital display
Color Option	White, Grey, Navy, Red, Khaki, Purple, Green etc.