




Foshan Shunde Green Motor Technology Co., Ltd.
 1#,Floor 4,Block 20,Huazhi Science & Innovation Center,No. 28,Sanle
 Road,East,Shunjiang Community,Beijiao 528311,Shunde,Foshan
 Web:www.greenmotortech.com Email: carrie@greenmotortech.com

OFFER SHEET

Model No.	GF2+ cargo tray			
Validation	30 days			
Payment Terms	50% T/T in advance, 50% T/T balance before delivery	Lead Time:	20 working days after receiving advance payment	
Loading quantity	2+tray, 8pcs/20GP, 18pcs/40HQ,			
Power				
Motor	AC 48V 5KW High efficiency			
Horsepower	7HP(5000W)			
Drive System				
Rear Axle	High efficiency gear drive, differential ratio 12.31:1, maintenance-free rear axle			
Battery	48V150Ah GEL battery. maintenance free type			
Body Chassis				
Chassis	Q355 steel frame stamping, welding molding, integral electrophoresis, outdoor epoxy + automobile grade protective armor paint			
Body	Ultralight special heat injection molding PP material, performance equivalent to the same level of car bumper split design anti-collision aging resistance			
Electrical System				
Controller	350A AC controller,CMOS continuously variable speed system			
Accelerator	Aluminum alloy all-in-one accelerator pedal, Hall-type acceleration system			
Suspension System				
Suspension	Macpherson independent suspension Rear suspension: tow suspension.			
Brake	Vehicle: oil brake front wheel disc brake + rear wheel drum brake + foot park brake			
Steering	Two-stage rack and pinion steering, meter			
Tyre、Seat				
Tyres	23*10.5-14, 4ply, off-road enlarged and widened tires + 14-inch aluminum alloy rims (more stable and more wear-resistant)			
Seat	PU+sponge foam technology seat sofa, anti-fouling and anti-aging			
Standard Configuration				
Dashboard	10-inch large-screen central control instrument, cigarette lighter, dual-port USB, ignition switch, direction selector switch, spot light switch			
Car stereo	two round stereos for loud speaker			
Windshield	folding windshield,			
Front basket	front basket			

Bumper	off-road front metal bumper		
Mirrors	side mirrors, inner mirror		
Optional Accessories			
LED light on the bumper	Aluminum alloy heat dissipation off-road vehicle special spotlight	USD 50	

Technical Specification			
Ground clearance	170mm	Min. turning radius	4m
Front/Rear wheel track	965/968mm	Max. Speed	30-40km/h
Front/Rear wheelbase	1670mm	Loading capacity	500kg
Size	3005mm*1345mm*2170mm	Gradeability	30%
Net weight	660kg	Mileage range	100-120km
Brake distance	3m	Charging time	8-10 hour



前后方向内尺寸690mm



左右方向内尺寸985mm



内部深度为220mm

